

# Product information

## megol Mehrzweckgetriebeöl GL 4 SAE 80W



### Description

High-grade gearbox oil with a wide range of uses for high tooth flank stresses. Gearbox oils of this type are recommended by motor vehicle and gearbox manufacturers for use in synchronised and nonsynchronised manual gearboxes, power units for building machinery, agricultural machinery and tractors and axle drives exposed to normal stresses.



### Approvals

API GL4 • MB-Approval 235.1 • ZF TE-ML 17A • ZF approval number ZF000068

### Meguin also recommends this product for vehicles that are subject to the following specifications

MIL-L 2105 • MAN 341 Typ E1 • MAN 341 Typ Z2

### Characteristic data

SAE class (gear oils)	80W SAE J306
Density at 15 °C	0,88 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	93,4 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	11,4 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -26 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	110 DIN ISO 2909
Pour point	-27 °C DIN ISO 3016
Flash point	218 °C DIN ISO 2592
Color number (ASTM)	3,5 DIN ISO 2049

### Available pack sizes

1 l Canister plastic	8609 GB-F-HR-RUS-GR
20 l Canister plastic	4374 D-GB
60 l Drum sheet metal	6366 D-GB
200 l Drum sheet metal	6527 D-GB
1.000 l Deposit container	9782 D-GB